Wattle/Log Straw/Excelsion

Wattle/Logs are man made cylinders of <u>either</u> compressed, weed free straw <u>or</u> Aspen Excelsior fibers. **Wattle/Logs** are encased in High-Density Polyethylene, photodegradable netting. **Wattle/Logs** are a leading sediment control BMP that is more durable and lower profile than silt fence as well as a better aesthetic and design value.







Quick Look


• Dimensions 9 in x 25 ft - 12 in x variable lengths

Netting
UV
High-Density Polyethylene
Added UV stabilizer

Straw Wattle/Log Material Specifications							
PROPERTY	ENGLISH		METRIC				
	9 in	12 in	22.86 cm	30.48 cm			
PHYSICAL							
Matrix Type	Straw (weed free)						
Mass/Unit Length	1.9 lbs/ft	2.75 lbs/ft	.09 kg/m	1.3 kg/m			
Diameter	8-9 in	10.5-12 in	20-23 cm	26-30 cm			
Length	25 ft	10 ft	7.6 m	3.08 m			
		20 ft		6.096 m			
Net Strand Thickness	0.0165 in	0.16 in	0.041 cm	0.04 cm			
Netting Weight	0.81 oz/yd	1.21 oz/yd	25 g/m	37.5 g/m			
Installed Free-Board Height	5.5-6.5 in	8-9 in	14-16.5 cm	20-23 cm			
Mesh Opening	0.5 in		1.27 cm				
Stretch Width	12.5 in	21 in	31.75 cm	53.3 cm			

Excelsior Wattle/Log Material Specifications						
PROPERTY	ENGLISH		METRIC			
	9 in	12 in	22.86 cm	30.48 cm		
PHYSICAL						
Matrix Type	100% Aspen Excelsior Fiber					
Mass/Unit Length	2.5 lbs/ft	3.0 lbs/ft	3.7 kg/m	4.5 kg/m		
Diameter	8-9 in	10.5-12 in	20-23 cm	26-30 cm		
Length	25 ft	10 ft	7.6 m	3.08 m		
		20 ft		6.096 m		
Net Strand Thickness	0.0165 in	0.16 in	0.041 cm	0.04 cm		
Netting Weight	0.81 oz/yd	1.21 oz/yd	25 g/m	37.5 g/m		
Installed Free-Board Height	5.5-6.5 in	8-9 in	14-16.5 cm	20-23 cm		
Mesh Opening	0.5 in		1.27 cm			
Stretch Width	12.5 in	21 in	31.75 cm	53.3 cm		

Dispose of unit in accordance with applicable Federal, state and local environmental laws and regulations. The user is solely responsible for the compliance with maintenance and disposal laws and regulations. The manufacturer or seller assumes no responsibility for proper or improper maintenance or disposal.



Phone (800) 808-1774 Fax (866) 990-1527 www.psibmp.com info@psibmp.com

